SINCE 1972 OWERLIFT JMBWAITERS ORPORATION www.dumbwaiters.com

20" Std. -Additional stops include 10' of height for each stop. 2-Stop overall height up to 20' included. oading-Overall Height to Floor

THE SMART WAY TO BUY A DUMBAN 3/4 HP, 110 V, 60Hz motor **UL classified elevator controller** Powder coated car, rail assembly, and trolley Call / Send stations

> Door locks & door safety switches (Hoistway doors are not included) Safety switch for motor access panel/door Adjustable limits

> > Top and bottom final limits

Custom car size at no charge up to a maximum of 30" x 30" x 30" or 15.63 cu.ft. Max.

Car can be open on any 3 sides at no charge. Fiberglass Reinforced Plastic (FRP) car skins


Motor can be on the bottom or on top. (Specify bottom or top motor mount when ordering)


Pillow block assembly opposite motor Size 40 roller chain (3,125 lb breaking strength)


Additional Options

Extra stops Fixed or adjustable shelves Stainless steel car Car gates Bi-parting car gates

Car here lights Keyed On/Off switch Elevator interlocks Hoistway doors 3/4 HP, 230 V, 60Hz motor 34 HP, 230 V, 50Hz motor for Europe







THE SMART WAY TO BUY A DUMBWAITER